



**36T ELECTRICAL RATING:**  
TYPICAL ELECTRICAL RATINGS TEMP RANGE: -40°F TO 350°F

**ROLLOUT SWITCHES**

- Auto and Manual Reset
- Offered in a Broad Temperature Range to Cover Most Heating Applications

Volts (VAC)	Resistive (Non-Inductive)	Motor Rating (Inductive)		
		Full Load	Locked Rotor	Pilot Duty
120	15A	3A	12A	125VA
240	10A	1.5A	6A	125VA

350°F Max Ambient Temperature

**SMALL FLUSH MOUNT SPST LIMIT THERMOSTATS STYLE 36TXE21 (FLUSH MOUNT AUTOMATIC ROLLOUT)**




Part No.	Terminals	Cut Out (°F)	Cut In (°F)	Diff.
SLF210HA	Horizontal 1/4"	210	170	40
SLF222VA	Vertical 1/4"	222	182	40
SLF230HA	Horizontal 1/4"	230	190	40
SLF250HA	Horizontal 1/4"	250	200	50

**AUTOMATIC ROLLOUTS SPST LIMIT THERMOSTATS STYLE 36TX11**



Part No.	Terminals	Cut Out (°F)	Cut In (°F)	Diff.
SLS140	45° angle 1/4"	140	100	40
SLS150	45° angle 1/4"	150	110	40
SLS160	45° angle 1/4"	160	120	40
SLS170	45° angle 1/4"	170	130	40
SLS180	45° angle 1/4"	180	140	40
SLS200	45° angle 1/4"	200	160	40
SLS300	45° angle 1/4"	300	250	50

**MANUAL ROLLOUTS SPST LIMIT THERMOSTATS STYLE 36TX16**



Part No.	Terminals	Cut Out (°F)	Cut In (°F)	Part No.	Terminals	Cut Out (°F)	Cut In (°F)
SRL130	Vertical 1/4"	130	Manual	SRL250	Vertical 1/4"	250	Manual
SRL135	Vertical 1/4"	135	Manual	SRL260	Vertical 1/4"	260	Manual
SRL220	Vertical 1/4"	220	Manual	SRL300	Vertical 1/4"	300	Manual
SRL230	Vertical 1/4"	230	Manual	SRL350	Vertical 1/4"	350	Manual
SRL240	Vertical 1/4"	240	Manual				

**SRL SERIES CROSS REFERENCE**

SUPCO Part No.	Replaces
SRL130	Rheem®/Ruud Weatherking® 47-22453-01
SRL135	Rheem®/Ruud Weatherking® 47-22453-02
SRL220	Nordyne® 626354
SRL230	Nordyne® 626353
SRL240	Nordyne® 626355
SRL250	Nordyne® 626352

SUPCO® Part No.	Replaces
SRL260	Nordyne® 626350
SRL300	Nordyne® 626343 Rheem®/Ruud Weatherking® 47-22861-02
SRL350	Goodman® B13701-54