



## Magnetic Tape Measures

Malco's "Magnetic Tip" tape measures are ideal for every ferrous metal working project! A powerful magnet and self-supporting 1 in. (25.4 mm) wide blade makes one-person measurements and measuring elevations an easy task.



Zero commencement: when hanging and pulling magnet, deduct 1/16 in. from measurement.



## Non-Magnetic Tape Measures



Malco's non-magnetic tape measures offered in 25 in. and 30 in lengths. Both tape measures have a 1 in wide blade with a double riveted tip connection. A rubber-clad housing ensures toughness for everyday use.

### Specifications

| Tape Measures  |  |                 |                |                             |                 |
|----------------|--|-----------------|----------------|-----------------------------|-----------------|
| Catalog Number | Description                              | Net Wt. oz. (g) | Catalog Number | Description                 | Net Wt. oz. (g) |
| T416M          | 1 in. x 16 ft. Magnetic Tip Tape Measure | 10 (284)        | CT425          | 1 in. x 25 ft. Tape Measure | 13 (369)        |
| T425M          | 1 in. x 25 ft. Magnetic Tip Tape Measure | 14 (397)        | CT430          | 1 in. x 30 ft. Tape Measure | 16 (454)        |
| T430M          | 1 in. x 30 ft. Magnetic Tip Tape Measure | 17 (482)        |                |                             |                 |

## Rotary Percussion Bits



Use in any rotary or rotary percussion drilling device for unexcelled performance in brick, tile, granite, concrete, masonry and other similar hard and dense materials. Brazed tungsten carbide tips have 120° chamfer and are specially tempered for strength and long life.

### Specifications

| Carbide Tipped Rotary Percussion Bits |                           |                              |                |                  |
|---------------------------------------|---------------------------|------------------------------|----------------|------------------|
| Catalog Number                        | Description               | Nominal Overall Length (in.) | Bit Dia. (in.) | Shank Dia. (in.) |
| RP01                                  | Carbide Tipped Rotary Bit | 3                            | 1/8            | 1/8              |
| RP04                                  | Carbide Tipped Rotary Bit | 3-5/16                       | 3/16           | 3/16             |
| RP09                                  | Carbide Tipped Rotary Bit | 4                            | 1/4            | 1/4              |
| RP10                                  | Carbide Tipped Rotary Bit | 6                            | 1/4            | 1/4              |

## Electrical Pliers

Cutter / Stripper / Crimper

Up front scissors action strips copper wire clean and easily cuts sizes 10 thru 20.

Bolt cutters leave a perfect rethread. Plier nose features serrated jaw and slim profile for pulling and putting loops on wire. Crimps all insulated and non-insulated solderless terminals including 7-8 mm auto. Lifetime pivot point assures greater joint strength and adds easy, precise adjustment capability. Black oxide, satin finish steel. Extra large red vinyl cushion grips.



### Specifications

| Electrical Pliers |   |                |                        |                    |                      |                |                 |                     |                    |
|-------------------|---|----------------|------------------------|--------------------|----------------------|----------------|-----------------|---------------------|--------------------|
| Catalog Number    | Description                                   | Capacities AWG | Capacities Metric (mm) | Capacities Bolt    | Capacities Cutting   | Crimping Gauge | Stripping Gauge | O/A Length in. (mm) | Net Weight oz. (g) |
| WSC8              | Electrical Pliers Cutter / Stripper / Crimper | —              | —                      | 4-40 / 5-40 / 6-32 | 8-32 / 10-32 / 10-24 | 22-10 ga.      | 22-10 ga.       | 8-1/4 (210)         | 8 (226)            |