

AC Axial Fans

80mm x 80mm x 38mm (3.15" x 3.15" x 1.5")

- Mounting Centres 71.5mm (2.82")

Part #	Watts	Volts	CFM	RPM	Bearing	Impeller	Noise	Connection	Weight
RF200	10	115	32	3100	Sleeve	Metal	34db (A)	Wire Leads	420g
RF201	9	115	21	2000	Sleeve	Metal	26db (A)	Wire Leads	420g
RF202	10	230	32	3100	Ball	Metal	34db (A)	Wire Leads	420g

120mm x 120mm x 38mm (4.72" x 4.72" x 1.5")

- Mounting Centres 105mm (4.13")

Part #	Watts	Volts	CFM	RPM	Bearing	Impeller	Noise	Connection	Weight
RF205	22	115	106	3000	Sleeve	Metal	50db (A)	Terminal	600g
RF210	22	115	106	3000	Ball	Metal	50db (A)	Terminal	600g
RF225	22	115	106	3000	Ball	Metal	50db (A)	Wire Leads	600g
RF215	21	230	106	3000	Sleeve	Metal	50db (A)	Terminal	600g
RF220	21	230	106	3000	Ball	Metal	50db (A)	Terminal	600g

119mm x 119mm x 38mm (4.69" x 4.69" x 1.5")

- Mounting Centres 105mm (4.13")

Part #	Watts	Volts	CFM	RPM	Bearing	Impeller	Noise	Connection	Weight
RF230	12	115	106	3100	Sleeve	Plastic	46db (A)	Terminal	530g
RF235	12	115	106	3100	Ball	Plastic	46db (A)	Terminal	530g
RF236	15	230	106	3100	Sleeve	Plastic	46db (A)	Terminal	530g
RF237	15	230	106	3100	Ball	Plastic	46db (A)	Terminal	530g

150mm x 150mm x 55mm (5.9" x 5.9" x 2.2")

- Mounting Centres 162mm (6.38")

Part #	Watts	Volts	CFM	RPM	Bearing	Impeller	Noise	Connection	Weight
RF240	42	115	230	3400	Ball	Plastic	53db (A)	Wire Leads	1kg
RF245	40	230	230	3400	Ball	Plastic	53db (A)	Wire Leads	1kg

150mm x 172mm x 38mm (5.9" x 6.7" x 1.5")

- Mounting Centres 162mm (6.38")

Part #	Watts	Volts	CFM	RPM	Bearing	Impeller	Noise	Connection	Weight
RF247	28	115	212	3400	Ball	Plastic	58db (A)	Terminal	720g
RF248	26	230	212	3400	Ball	Plastic	58db (A)	Terminal	720g

180mm x 180mm x 90mm (7.1" x 7.1" x 3.5")

- Mounting Centres 152.7mm (6.01")

Part #	Watts	Volts	CFM	RPM	Bearing	Impeller	Noise	Connection	Weight
RF249	72	115	460	3400	Ball	Plastic	59db (A)	Screw	2.2kg

254mm x 254mm x 89mm (10" x 10" x 3.5")

- Mounting Centres 247mm (9.72")

Part #	Watts	Volts	CFM	RPM	Bearing	Impeller	Noise	Connection	Weight
RF250	35	115	547	1650	Ball	Plastic	55db (A)	Terminal	1.9kg
RF255	33	230	547	1650	Ball	Plastic	55db (A)	Terminal	1.9kg

Axial Fan Features:

- Die-cast Aluminum Housing
- Shaded Pole Motor
- Impedance Protection
- CSA & UL Approved.
- Operating Temp. Range -10°C to 70°C
- Metal or Plastic Impellers
- Sleeve or Ball Bearings



T8-RF210

T8-RF200



T8-RF230



T8-RF245



T8-RF250

Blowers

Metal Fan Guards

Part #	Size
T8-CFG-60M	66mm
T8-CFG-80M	80mm
T8-CFG-92M	92mm
T8-CFG-120M	120mm
T8-CFG-150M	150mm
T8-CFG-254M	254mm

Plastic Fan Guards

Mounting: Plastic Tabs

Part #	Size
T8-CFG-80P	80mm
T8-CFG-120P	120mm

Note: T8-CFG-80M, 120M, 150M are also available in black. *

T8-CFC-T24



Axial AC Power Cords

Bare Wire - 2 Pin molded connection to bare wire leads.

Plug - 2 Pin molded connection to 2 prong plug.

Bare Wire	Description	Plug
T8-CFC-T24	60.96cm (24") Cord	T8-CFC-T24P
T8-CFC-T48	121.92cm (48") Cord	T8-CFC-T48P
T8-CFC-T72	182.88cm (72") Cord	T8-CFC-T72P

Rotation determined opposite shaft end
Double shaft determined at lead end

Shaft length measured from hub
face to shaft end