

EXTREME STANDARD TIPS

A full series of manual lighting tips can be used with any Air Acetylene torch handle (PLF-A5 or G-4). Add range to your torch kit with economical tips that also feature a removable orifice screw.



A-2
(0386-0100)



A-3
(0386-0101)



A-5
(0386-0102)



A-8
(0386-0103)



A-11
(0386-0104)




A-14
(0386-0105)



A-32
(0386-0106)



MSA-8
(0386-0365)



Tip No.	Tip Size		Gas Flow		Soft Solder		Silver Braze		Replacement Orifice Model
	IN.	MM	@14 PSI SCFH	(0.9 BAR) M3/HR	IN.	MM	IN.	MM	
A-2	1/8	4.8	2.0	0.06	1/8-1/2	3-15	1/8-1/4	3-10	OR-A2
A-3	3/16	6.4	3.6	0.108	1/4-1	10-25	1/8-1/2	3-12	OR-A3
A-5	1/4	7.9	5.7	0.171	3/4-1 1/2	20-40	1/4-3/4	10-20	OR-A5
A-8	5/16	9.5	8.3	0.249	1-2	25-50	1/2-1	15-25	OR-A8
A-11	7/16	11.1	11.0	0.33	1 1/2-3	40-75	7/8-1 5/8	20-40	OR-A11
A-14	1/2	12.7	14.5	0.435	2-3 1/2	50-90	1-2	30-50	OR-A14
A-32	3/4	19.0	33.2	0.996	4-6	100-150	1 1/2-4	40-100	OR-A32
MSA-8	3/8	9.5	5.8	0.174	3/4-3	20-75	1/4-3/4	10-20	OR-A5

Professional Tip Pack (0386-0577)

Includes these air acetylene tips: A-8, A-5 and A-2 plus a striker and an 8" x 12" Torch Shield made with PyroSil™.