



Gas Test Gauges

Use to pressure test all new installations for leaks and inspection codes. After installation and the system has been pressurized, the leakage will be indicated by a pressure drop on the gauge.



TGB6



TGH30
Side Mount



GP210-5



TGB30
Top Mount

| | Replacement Gauge | 1/2" FPT | *Top Mount 3/4" FPT | 1" FPT | Side Mount 3/4" FPT |
|---|-------------------|----------|---------------------|---------|---------------------|
| 15 psi, 2" 1/10 lb. incr. Full Scale | GP210-5 | TGB215 | TGB15 | TGB115 | TGH15 |
| 30 psi, 1/2 lb. incr., 2" | GP211-5 | TGB230 | TGB30 | TGB130 | TGH30 |
| 60 psi, 1 lb. incr., 2" | GP212-5 | TGB260 | TGB60 | TGB160 | TGH60 |
| 100 psi, 1 lb. incr., 2" | GP213-5 | TGB2100 | TGB100 | TGB1100 | TGH100 |
| **0-6 psi/1/10 lb., 0-12 in. of Mercury, 4" [100mm] | GD408IP | TGB206 | TGB6 | TGB106 | TGH6 |
| 0-15 psi/1/10 lb., 0-30 in. of Mercury, 4" [100mm] | GS410-5IP | TGB4215 | TGB415 | TGB4115 | TGH415 |

**Special sensitive 2 1/2" diaphragm gauge for more accurate low pressure reading.

*Uniweld reserves the right to use either plated steel or an aluminum hex body when supplying a top mount gas test gauge assembly.

Water Test Gauges

| Part# | Description | Replacement Parts and Gauges | Description |
|----------|---|------------------------------|--|
| TGW300 | Water test gauge with 3/4" female hose connection, 2 1/2" gauge, 300 PSI | TGW | 3/4" FHT x 1/4" female NPT connection only |
| TGW300DP | Water test gauge with 3/4" female hose connection, 2 1/2" gauge, 300 PSI Drag Pointer | GS316-5 | 2 1/2", 300 PSI, 12 o'clock dial |
| | | GS316-5DP | 2 1/2", 300 PSI, 12 o'clock dial, Drag Pointer |



TGW300DP

Gauges/Thermometers

