



## OIL FIRED UPFLOW FURNACE SPECIFICATIONS

<b>MODEL NO.</b>	<b>VH8FA119P60B VH8FA119T60B (BECKETT AFG)</b>		
<b>HEATING CAPACITY</b>	High Fire	* Med Fire	Low Fire
<b>HEAT INPUT RATE (BTUH)</b>	156,250	140,000	119,000
<b>OUTPUT BTUH<sup>1</sup></b>	132,000	119,000	101,000
<b>SEASONAL EFFICIENCY<sup>2</sup></b>	* 85.0%		
<b>LARGEST REC A/C<sup>3</sup></b>	5 Tons		
<b>NOMINAL TEMP RISE</b>	66°	66°	66°
<b>BIO FUEL APPROVAL</b>	B20		
<b>CASING HEIGHT (IN.):</b>	50-1/8"		
<b>CASING WIDTH (IN.):</b>	24-1/2"		
<b>CASING DEPTH (IN.):</b>	36-1/2"		
<b>NOMINAL FLUE OUTLET DIA.</b>	7"		
<b>APPROX SHIPPING WEIGHT (LBS)</b>	316		
<b>APPROVAL AGENCY</b>	ETL		
<b>QTY AND SIZE OF PERMANENT FILTERS</b>	(1) 24-3/4" X 19-3/4"		
<b>ELECTRICAL REQUIREMENTS</b>	120/60/1		
<b>MAX FUSE SIZE</b>	20		
<b>TOTAL CURRENT (AMPS) PSC / CTM</b>	16 / 14.1		
<b>HEIGHT FROM FLOOR TO CENTER OF FLUE</b>	42-3/4"		
<b>SUPPLY AIR OUTLET SIZE (W-IN. X D-IN.)</b>	20" X 20"		
<b>RETURN AIR DUCTWORK CONNECTION FLANGE SIZE ON FILTER RACK (D-IN. X H-IN.)</b>	23-3/4" X 19"		
<b>RETURN AIR INLET OPENING SIZE IN SIDE CASING (TO BE CUT-OUT BY DEALER) (D-IN. X H-IN.)</b>	23" X 16-3/8"		
<b>FIELD VENT TERMINATION KIT</b>	AOPS8414		
<b>SIDEWALL VENT ACCESSORIES KIT</b>	AOPS8394		
<b>COMBUSTION AIR KIT FOR BECKETT</b>	AOPS8397		
<b>BLOCKED VENT KIT<sup>4</sup></b>	350156		
<b>SUPPLY PLENUM</b>	PK202X202		
<b>RETURN BOOT &amp; DROP KIT</b>	RD2512X2520		
<b>CASED COIL 2-3 TON</b>	HE33936PA212		
<b>CASED COIL 2-3 TON HIGH EFF.</b>	HE47936PA212		
<b>CASED COIL 3.5-5 TON</b>	HE50960PA212		

\* AS SHIPPED SETTING

**- SEE NEXT PAGE FOR MORE DATA -**

<sup>1</sup> OUTPUT BTUH BASED ON ANNUAL FUEL UTILIZATION EFFICIENCY RATED BY MANUFACTURER.

<sup>2</sup> SEASONAL EFFICIENCY (ALSO CALLED AFUE - ANNUAL FUEL UTILIZATION EFFICIENCY) RATINGS ARE BASED ON TESTS FOLLOWING U.S. DEPARTMENT OF ENERGY TEST PROCEDURES.

<sup>3</sup> TO PERMIT LARGEST RECOMMENDED AIR CONDITIONING (AT .5 STATIC PRESSURE), SELECTION OF THE HIGHEST MOTOR SPEED IS REQUIRED.

**ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.**

<sup>4</sup> NOT TO BE USED IN SIDEWALL VENT APPLICATIONS, USE ONLY WHEN CHIMNEY VENTED.

## OIL FIRED UPFLOW FURNACE SPECIFICATIONS

Model Number Digit	1	2	3	4	5	6	7	8	9	10	11	12
	Brand	Configuration	Heat Exchanger Identifier	Flue	Design Change	Capacity	Capacity	Capacity	Blower Motor Type	Airflow Capacity for Cooling	Airflow Capacity for Cooling	Burner
<b>Oil Furnace Model Nomenclature</b>	V	H	8	F	A	1	1	9	P	6	0	B
<b>Example Model Numbers</b>	V	H	8	F	A	1	1	9	T	6	0	B
<b>V= Spirit</b>	V											
<b>H = Highboy</b>		H										
<b>8= Heat Exchanger Identifier</b>			8									
<b>F = Vertical Front Flue</b>				F								
<b>Design Change</b>					A							
<b>Heating Output MBTUH (000's) – factory shipped</b>						1	1	9				
<b>P = PSC<sup>1</sup>, T = CTM<sup>2</sup></b>									P			
<b>Airflow: 60MBTUH = 5 Tons @ 400cfm/ton</b>										6	0	
<b>B = Beckett AFG</b>												B

- SEE NEXT PAGE FOR MORE DATA -

<sup>1</sup> PSC = PERMANENT SPLIT CAPACITOR  
<sup>2</sup> CTM = CONSTANT TORQUE MOTOR E.C.M.

## OIL FIRED UPFLOW FURNACE SPECIFICATIONS

<b>BLOWER DATA:</b>	<b>VH8FA119P60B</b>	<b>VH8FA119T60B</b>
<b>BLOWER MODEL</b>	<b>DD 12-11T</b>	<b>DD 12-11T</b>
<b>MOTOR H.P.</b>	3/4 HP	1 HP
<b>MOTOR TYPE &amp; NUMBER OF SPEEDS</b>	PSC - 4	CTM - 5
<b>HIGH SPEED AIRFLOW (SCFM) @ 0.5 IN. W.G. EXTERNAL STATIC PRESSURE:</b>	2069	2045
<b>Diameter x Width</b>	11 x 11	11 x 11

<b>BURNER DATA</b>	<b>BECKETT "AFG" S - PLATE 3383 (2-3/4U) 31517 CERAMIC</b>		
<b>AIR TUBE LENGTH (IN.)</b>	4 1/2"		
<b>BURNER HEAD TYPE:</b>	F6		
<b>FUEL TYPE / BIO APPROVAL:</b>	#2 / B20		
<b>NOZZLE RATING (GPH):</b>	1.10	1.00	0.85
<b>SPRAY ANGLE (DEG.):</b>	80°	80°	80°
<b>SPRAY PATTERN:</b>	HOLLOW (A)	HOLLOW (A)	HOLLOW (A)
<b>OIL PUMP PRESSURE (PSIG):</b>	120 PSI		
<b>COMBUSTION CHAMBER TYPE:</b>	REFRACTORY (SOFT FIBER)		

<b>CLEARANCES</b>	
	<b>MINIMUM CLEARANCES TO COMUSTIBLE MATERIALS:</b>
<b>SIDES</b>	0"
<b>FRONT (SERVICE ACCESS)</b>	24"
<b>REAR</b>	0"
<b>FLUE</b>	8"
<b>TOP PLENUM</b>	1"

- SEE NEXT PAGE FOR MORE DATA -

# OIL FIRED UPFLOW FURNACE SPECIFICATIONS

## VH8FA119P60B

ALTERATIONS REQ'D FOR A/C @ DESIGN EXTERNAL STATIC PRESSURE				
COOLING UNIT	HTG Speed by Input			Recommended CLG Speed
	Low Fire	Mid Fire	High Fire	
36,000	Low	ML	MH	Low
42,000	Low	ML	MH	Med Low
48,000	Low	ML	MH	Med High
60,000	Low	ML	MH	High

AS SHIPPED CLG. →

Speed Tap\ Static Pressure	Furnace Airflow (CFM) vs. External Static pressure (in. WC.)						
	0.1	0.2	0.3	0.4	0.5	0.6	0.7
Low	1308	1300	1274	1265	1237	1169	1127
ML	1583	1526	1515	1491	1458	1420	1371
MH	1894	1874	1839	1804	1746	1683	1632
High	2254	2228	2195	2181	2069	1995	1897
Furnace Motor Current Draw (Amps/Watts) vs. External Static pressure (in. WC.)							
Low	7.56 698	6.99 660	6.66 637	6.50 623	6.21 602	5.91 578	5.83 568
ML	9.21 867	8.44 801	8.19 786	8.01 772	7.61 745	7.28 715	6.93 687
MH	10.6 1040	10.2 999	9.87 971	9.38 923	9.01 895	8.68 864	8.23 829
High	13.5 1320	13.2 1290	12.8 1270	12.4 1240	11.3 1130	10.7 1090	10.2 1020

Speed Tap\ Static Pressure	High Fire Temperature Rise vs. External Static pressure (in. WC.)						
	0.1	0.2	0.3	0.4	0.5	0.6	0.7
Low	94	94	96	97	99	105	108
ML	78	80	81	82	84	86	90
MH	65	66	67	68	70	73	75
High	54	55	56	56	59	62	65

AS SHIPPED HTG. →

Speed Tap\ Static Pressure	Mid Fire Temperature Rise vs. External Static pressure (in. WC.)						
	0.1	0.2	0.3	0.4	0.5	0.6	0.7
Low	84	84	86	87	89	94	98
ML	70	72	73	74	76	78	80
MH	58	59	60	61	63	65	68
High	49	49	50	51	53	55	58

Speed Tap\ Static Pressure	Low Fire Temperature Rise vs. External Static pressure (in. WC.)						
	0.1	0.2	0.3	0.4	0.5	0.6	0.7
Low	72	72	73	74	76	80	83
ML	59	61	62	63	64	66	68
MH	49	50	51	52	54	56	57
High	42	42	43	43	45	47	49

- SEE NEXT PAGE FOR MORE DATA -

## OIL FIRED UPFLOW FURNACE SPECIFICATIONS VH8FA119T60B

ALTERATIONS REQ'D FOR A/C @ DESIGN EXTERNAL STATIC PRESSURE				
COOLING UNIT	HTG Speed by Input			Recommended CLG Speed
	Low Fire	Mid Fire	High Fire	
36,000	ML	Med	MH	Low
42,000	ML	Med	MH	Med Low
48,000	ML	Med	MH	Med High
60,000	ML	Med	MH	High

AS SHIPPED CLG. →

Speed Tap\ Static Pressure	Furnace Airflow (CFM) vs. External Static pressure (in. WC.)						
	0.1	0.2	0.3	0.4	0.5	0.6	0.7
Low	1520	1429	1385	1311	1222	1139	1085
ML	1660	1593	1536	1491	1422	1369	1295
Med	1749	1693	1652	1572	1520	1465	1391
MH	1827	1766	1692	1674	1596	1540	1487
High	2253	2185	2142	2114	2045	1991	1955
Speed Tap\ Static Pressure	Furnace Motor Current Draw (Amps/Watts) vs. External Static pressure (in. WC.)						
	0.1	0.2	0.3	0.4	0.5	0.6	0.7
Low	2.62 211	2.81 228	2.92 237	3.07 253	3.22 268	3.35 279	3.46 289
ML	3.34 279	3.55 294	3.72 310	3.84 325	4.02 339	4.13 350	4.31 364
Med	3.74 314	3.91 327	4.11 345	4.25 360	4.39 374	4.60 390	4.74 406
MH	4.21 356	4.40 373	4.57 390	4.73 407	4.90 422	5.01 432	5.12 450
High	7.2 638	7.2 650	7.43 665	7.68 688	7.92 712	8.16 714	8.29 751

Speed Tap\ Static Pressure	High Fire Temperature Rise vs. External Static pressure (in. WC.)						
	0.1	0.2	0.3	0.4	0.5	0.6	0.7
Low	80	85	88	93	99	105	112
ML	73	76	79	81	85	89	94
Med	69	72	73	77	80	83	87
MH	66	69	72	72	76	79	82
High	54	56	57	57	59	61	62

AS SHIPPED HTG. →

Speed Tap\ Static Pressure	Mid Fire Temperature Rise vs. External Static pressure (in. WC.)						
	0.1	0.2	0.3	0.4	0.5	0.6	0.7
Low	72	77	80	84	90	97	102
ML	66	69	72	74	77	80	85
Med	63	65	67	70	73	75	79
MH	60	62	65	66	69	72	74
High	49	50	51	52	54	55	56

Speed Tap\ Static Pressure	Low Fire Temperature Rise vs. External Static pressure (in. WC.)						
	0.1	0.2	0.3	0.4	0.5	0.6	0.7
Low	62	66	68	71	77	82	86
ML	56	59	61	63	66	68	72
Med	54	55	57	60	62	64	67
MH	51	53	55	56	59	61	63
High	42	43	44	44	46	47	48

- SEE NEXT PAGE FOR MORE DATA -

# OIL FIRED UPFLOW FURNACE SPECIFICATIONS

