Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance			Mechanical		
Evaporator Temp. (°F)	45.00	50	Displacement (in^3/Rev):	3.40	
Condensing Temp. (°F)	130.00	115	Displacement (ft^3/Hr):	412.6	
Return Gas Temp. (°F)	65.00	70	Overall Length (in):	9.56	
Liquid Temp. (°F)	115.00	100	Overall Width (in):	9.66	
Capacity (BTU/hr)	61000	74900	Overall Height (in):	17.35	
Power (W):	5660	4570	Mounting Length (in):	7.50	
Current (Amps):	16.05	13.45	Mounting Width (in):	7.50	
EER(BTU/Wh):	10.8	16.4	Mounting Height (in):	17.62	
Mass Flow (lbs/hr):	899	998	Suction Size (in),Type:	7 / 8 Stub	
Sound Data @ 45 / 130			Discharge Size (in),Type:	1 / 2 Stub	
Sound Power (dBA):	72 Avg	77 Max	Initial Oil Charge (oz):	42	
Vibration mils(peak-peak):	2.0 Avg	3.0 Max	Oil Recharge (oz):	36	
Record Date:	2017-03-02		Oil Type:	ЗМА	
			Net Weight (lbs):	75.6	
			Internal Free Volume (in^3):	190.8	
			Horse Power: *Overall compressor height on Copeland Brand F mounting grommets.	Product's specified	
Electrical			Capacitors		
LRA High* (Amps):		136.0	Type Part No Low MFD High MFD Volts	User Description	
LRA Low*(Amps):			No data available in table		
LRA Half Winding (Amps):					
MCC (Amps):		27.4			
Max Operating Current (Amps):		27.0			
RLA, MCC/1.4(use for contactor selection)(Amps):		19.6			
RLA, MCC/1.56(use for breaker & Dreaker & Strain St		17.6			
RPM:		3500			
Box IP :		21			
UL File No:		SA-2337			
UL File Date:		2014-03- 21			
*Low and High refer to the low and high nominal voltage ranges for					

which the motor is approved.

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-410A HFC	200/220	3	50	Air Conditioning
R-410A HFC	200/220	3	50	A/C, 67% Load Of Compressor Model
R-410A HFC	200/230	3	60	A/C, 67% Load Of Compressor Model